

# Figure 4® Standalone

Ultra-fast and affordable industrial 3D printer



Part of 3D Systems' scalable, fully integrated Figure 4 technology platform, Figure 4 Standalone is an affordable and versatile solution for low volume production, and same-day prototyping for fast design iteration and verification, offering speed, quality and accuracy with industrial-grade durability, service and support.

# Figure 4® Standalone

Ultra-fast and affordable industrial 3D printer




## AFFORDABILITY:

Industrial-grade durability at an affordable price



## VERSATILITY:

Performance from a variety of materials



## SPEED:

Fast throughput speed for accelerated “parts-in-hand” delivery



## TOTAL COST OF OPERATIONS:

Cost efficient parts production



## FAST TURNAROUND

Achieve same-day functional prototyping and low volume production for output volumes of up to 500 parts per month, with ultra-high speeds up to 100 mm/hour.



## EASE OF USE

Figure 4 Standalone was designed for ease-of-use, and includes file preparation and print management with the powerful 3D Sprint® software, quick and easy material changes with a manual material feed, and a separate post-processing accessory available for curing.



## CONSISTENT, HIGH QUALITY OUTPUT

Powered by non-contact membrane Figure 4 technology, Figure 4 Standalone offers quality and accuracy at six sigma repeatability, with exceptional surface finish and fine feature detail. With a compact and easy-to-use design, Figure 4 Standalone delivers industrial-grade durability, service, and support with an Advanced Service Exchange model and 3D Connect™ for proactive and preventative support.



## WIDE RANGE OF APPLICATIONS

With Figure 4 Standalone versatility, you can use the same printer for rapid iteration, functional prototyping, design verification, end-use parts for low volume production and replacement parts, digital texturing applications, jewelry casting patterns, rapid tooling of molds, master patterns, jigs and fixtures.



## Wide Range of Materials for Application Diversity

3D Systems' Material Design Center has over 30 years of proven R&D experience and process development expertise. The broad and expanding range of materials available for Figure 4 Standalone addresses a wide variety of applications needs, for functional prototyping, direct production of end-use parts, molding and casting.

### RIGID MATERIALS

Figure 4 rigid materials produce durable plastic parts with the look and feel of cast or injection molded parts, with features that include fast print speeds, high elongation, exceptional impact strength, humidity/moisture resistance, long-term environmental stability and more.

### ELASTOMERIC MATERIALS

Figure 4 elastomeric materials are ideal for the production of functional rubber-like parts with excellent shape recovery, high tear strength, great for compressive applications and material malleability.

### HIGH TEMPERATURE MATERIAL

With heat deflection temperatures up to over 300° C with no additional thermal post-cure required, Figure 4 heat resistant material offers high rigidity and exceptional stability under extreme conditions.

### SPECIALTY MATERIALS

Choose from Figure 4 specialty materials for sacrificial tooling, jewelry casting, medical applications requiring biocompatibility and/or sterilization, and more.

## Accessories

### LC-3DPRINT BOX UV POST-CURING UNIT

The optional LC-3DPrint Box post-curing unit is available for UV-curing parts, required to obtain the final material properties, and is the recommended UV-curing unit for Figure 4 Standalone print materials. The LC-3DPrint Box is a revolutionary UV light box equipped with 12 UV light bulbs strategically placed inside to ensure a product is illuminated from all sides, which results in a quick and uniform curing cycle. This light-based UV curing process takes minutes versus hours with heat-based curing processes.

### LC-3DMIXER FROM 3D SYSTEMS

The optional LC-3DMixer keeps your Figure 4 materials ready for use at any time at an optimum consistency. The LC-3DMixer is a roller/tilting stirring device for mixing 3D printing materials.



## Figure 4® Standalone

PRINTER HARDWARE	
<b>Build Volume</b> (xyz)	124.8 x 70.2 x 196 mm (4.9 x 2.8 x 7.7 in)
<b>Resolution</b>	1920 x 1080 pixel
<b>Pixel Pitch</b>	65 microns (0.0025 in) (390.8 effective PPI)
<b>Wavelength</b>	405 nm
<b>Operating Environment</b> Temperature Humidity (RH)	18-28 °C (64-82 °F) 20-80%
<b>Electrical</b>	100-240 VAC, 50/60 Hz, Single Phase, 4.0A
<b>Dimensions</b> (WxDxH) 3D Printer crated Pedestal crated 3D Printer uncrated 3D Printer + Pedestal uncrated	73.66 x 68.58 x 129.54 cm (29 x 27 x 51 in) 82.55 x 79.375 x 55.245 cm (32.5 x 31.25 x 21.75 in) 42.6 x 48.9 x 97.1 cm (16.7 x 19.25 x 38.22 in) 68.1 x 70.4 x 135.6 cm (26.8 x 27.71 x 53.38 in)
<b>Weight</b> 3D Printer crated Pedestal crated 3D Printer uncrated 3D Printer + Pedestal uncrated	59 kg (130 lbs) 26.3 kg (58 lbs) 34.5 kg (76 lbs) 54.4 kg (120 lbs)
<b>Certifications</b>	FCC, CE, EMC

ACCESSORIES	
<b>Post-Processing</b>	Includes part finishing tools accessory kit; Requires optional 3D Systems LC-3DPrint Box UV post-curing unit or other UV-curing unit
LC-3DPrint Box	Load capacity (WxDxH): 260 x 260 x 195 mm Dimensions (WxDxH): 41 x 44 x 38 cm Full light spectrum: 300-550 nm Controlled temperature for optimal curing Weight (uncrated): 22 kg Electrical: 110V/230V, 50/60 Hz, 2.6A/1.3A
<b>LC-3DMixer</b> (for mixing materials, purchase separately)	Dimensions (WxDxH): 410 x 270 x 100 mm Weight (uncrated): 4 kg Electrical: 100-240 V, 50/60 Hz

MATERIALS	
<b>Build Materials</b>	See material selector guide and individual material datasheets for specifications on available materials.
<b>Material Packaging</b>	1kg bottles for manual pour

SOFTWARE AND NETWORK	
<b>3D Sprint® Software</b>	Easy build job set-up, submission and job queue management; Automatic part placement and build optimization tools; Part nesting capability; part editing tools; Automatic support generation; Job statistics
<b>3D Connect™ Software Capable</b>	3D Connect Service provides a secure cloud-based connection to 3D Systems service teams for proactive and preventative support.
<b>Connectivity</b>	0/100/1000 Ethernet Interface
<b>Client Hardware Recommendation</b>	<ul style="list-style-type: none"> <li>3 GHz multiple core processor (2 GHz Intel® or AMD® processor mini) with 8 GB RAM or more (4 GB mini)</li> <li>OpenGL 3.2 and GLSL 1.50 support (OpenGL 2.1 and GLSL 1.20 mini), 1 GB video RAM or more, 1280 x 1024 (1280 x 960 mini) screen resolution or higher</li> <li>SSD or 10,000 RPM hard disk drive (minimum requirement of 7 GB of available hard-disk space, additional 3 GB free disk space for cache)</li> <li>Google Chrome or Internet Explorer 11 (Internet Explorer 9 mini)</li> <li>Other: 3 button mouse with scroll, keyboard, Microsoft .NET Framework 4.6.1 installed with application</li> </ul>
<b>Client Operating System</b>	Windows® 7 and newer (64-bit OS)
<b>Input File Formats Supported</b>	STL, CTL, OBJ, PLY, ZPR, ZBD, AMF, WRL, 3DS, FBX, IGES, IGS, STEP, STP and X_T

NOTE: Not all products and materials are available in all countries – please consult your local sales representative for availability.

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2019 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. 3D Systems, the 3D Systems logo, Figure 4 and 3D Sprint are registered trademarks and 3D Connect is a trademark of 3D Systems, Inc.